

Product Presentation



Application

This machine is design for all kinds of textile's perspiration resistance color fastness drying test, matching GT-D09 Perspiration Tester using. It also apply for high temperature heating & drying test for other products.



Feature

- Polished stainless-steel chamber.
- Latest PID controller.
- Uniform distribution of air temperature.
- Forced-air convection.
- Double Layer glass door, larger viewing window.



Standards

| | |
|---------------|--|
| Perspiration: | GB/ T 3922, AATCC 15, ISO105-E04, JIS L 0848 |
| Sea Water: | GB/ T5714, ISO105-E02, AATCC107 |
| Water: | GB/ T5713, ISO105 E01, AATCC106 |
| Saliva: | GB/ T 18886 |

Key Specification

| Model | GT-D10-30L | GT-D10-80L | GT-D10-136L | GT-D10-220L |
|---------------------------|---------------------|---------------|---------------|---------------|
| Interior Dimensions | 340*320*320mm | 450*400*450mm | 550*450*550mm | 600*500*750mm |
| Chamber Volume | 30L | 80L | 136L | 220L |
| Temperature Range | RT+10°C~250°C | | | |
| Display Resolution | 0.1°C | | | |
| Temperature Stability | ±1°C | | | |
| Ambient Temperature | +5~40°C | | | |
| Power Consumption | 850W | 1100W | 1550W | 2050W |
| Timing Range | 1~9999min | | | |
| Exterior Dimension(L×W×H) | 620*530*490mm | 740*618*630mm | 840*670*730mm | 880*720*930mm |
| Power Supply | 1 φ AC 220V 50/60HZ | | | |

Accessories

| | | |
|----------------------|------|------------|
| Standard accessories | 2pcs | Shelves |
| | 1pc | Power line |